

  
**aIRSTAR**




**Crystal Pixel Dynamic White**

# Crystal Pixel Dynamic White




## Technical data

Lighted area	22,000 ft <sup>2</sup> / 2,000 m <sup>2</sup>
Color temperature	Dynamic white: from 3,000 to 6,500 K
CRI	80
Flicker	3.1 kHz
Luminous flux	2 x 33,000 lm
LED lifetime	50,000 h
Power consumption	500 W
Power supply	100-240 VAC 50-60 Hz
Battery input - 52V / Backup power	<div> <b>PowerSwitch</b> (optional) <div>  <p>Smart Power Management: Automatically switches between AC/DC power sources to eliminate downtime and loss of light.</p> </div> </div> <div>New!</div>

Envelope diameter	4 ft (130 cm), 5 ft (160 cm), 6.5 ft (200 cm)
Wind resistance	Up to 30 mph (48 km/h)
Set-up time	< 15 minutes
Inflation	Fast and self-regulated inflation
Noise level	3 modes: silent, standard, high wind
Net weight of balloon + envelope	From 24 lbs (11 kg) to 27 lbs (12 kg)
Certifications	CE, IP 54
Light source	Airstar LED Matrix : 12 macro-pixels
Mesh network balloons	109 yd / 327 ft (100 m) between each balloon
Light controls	<p>&gt; via the <b>control panel on the product</b></p> <p>&gt; Remotely via the <b>Airstar Light app</b></p> <p>&gt; <b>DMX</b></p> <ul style="list-style-type: none"> <li>• DMX profiles available for major control surfaces</li> <li>• 5-pin DMX connectors &amp; CRMX</li> <li>• Macro mode: 4 to 16 channels</li> <li>• Pixel mode: 6 pixels/2 colors for 14 channels</li> </ul>

## Illumination



## Packaging

Shock-proof, wheeled case  
Dimensions : 31 x 18 x 13 in  
(81 x 47 x 35 cm)  
Total weight: less than 50 lb (23 kg)



## Accessories


Various stands  
Stand cover, black or white  
Sandbags  
Suspension kit  
Guying kit

## Customization

Vinyl graphics  
Coloured slipcovers  
Digitally printed envelopes

## Airstar Light App

Control your balloons easily and remotely!



Control up to 250 balloons



10 light animations available

