

TUBE 3,200 W NEW

Helium & Air

Technical data

Light source	LED RGBAwWcW
CCT	2,800 K to 6,500 K
CRI	96>98
TCLI	98+
LED lifetime	50,000 hrs
Power supply (PSU)	110-240 VAC 50-60 Hz
Nb Power supply unit	4
Power supply dimensions	14 x 6 x 3 in / 37 x 15 x 7 cm
Power supply weight	12.5 lbs / 5.7 kg
Power consumption	3,200 W
IP Protection	IP65
Noise level	Noiseless
Mesh network balloons	109 yd (100 m) between each balloon



Light controls

- > via the **control panel on the product**
- > Remotely via the **Airstar Light app**
- > **DMX**
 - DMX profiles available for major control surfaces
 - 5-pin DMX connectors & **CRMX**



Airstar Light App

Control your balloons easily and remotely!



Control up to
250 balloons



8 light animations
available



AIRSTAR
LIGHT

Available on the
App Store

Available on the
Google Play

Packaging

Flight case

Dimensions: 47 x 24 x 29 in
120 x 60 x 74 cm

Transport gross weight: 210 lbs (95 kg)



Included accessories

Guy rope set, skirt, 65 ft (20 m) extension,
helium cylinder connection

Envelope

Envelope dimensions	110.6 x 196.8 in / 281 x 500 cm
Volume	1179.5 ft ³ / 33.4 m ³
Net weight of the balloon	52 lbs / 23.6 kg
Certifications	CE, IP65



Illumination



Height 24.5 ft (7.5 m)

0 1 2 3 4 5 6 7 8 9 10 m

3,200 K	358	342	338	309	272	234	198	163	136	114	94	lux
	33.2	31.7	31.4	28.7	25.3	21.7	18.4	15.1	12.6	10.6	8.8	fc
5,600 K	376	382	366	334	294	253	212	176	146	122	101	lux
	34.9	35.5	34.0	31.0	27.3	23.5	19.7	16.3	13.5	11.3	9.4	fc

