Sirocco 1000



Weight and Dimensions

Net weight of the balloon	18 lbs 8.6 kg
Envelope size	ø 45 in / h 25 in
	ø 116 cm / h 64 cm

Packaging

Included: Lighting balloon with 1x standard envelope (without stand), 1x power cord (30 ft | 9.2 m), 1x quick-start guide, 1x envelope repair kit

Transport bag	42 x 11 x 11 in (L*w*h)
	$108 \times 30 \times 30 \text{ cm (L*w*h)}$
Transport gross weight	Less than 34 lbs 15.5 kg

Recommended Accessories

Height from 55 in (140 cm) to 189 in (480 cm) Stand 15 ft

Weight 30 lbs | 13.5 kg

Sandbag Weight (with sand): 25 lbs (x3 bags recommended)

Main options -----

Envelope options: FLEX (for permanent or long-term use), lenticular, reversed reflector, branded with logo, customized reflector color






Lighting Data

Light Engine	Airstar LED Matrix: 18 x 5 500 lm
Maximum Lumens	99,000 lm
Average LED Life *	50.000 h
Color Temperature: Daylight	5.000 K
CRI	70
Light under the balloon **	61 fc / 660 lx

(13 ft high | 4 m)



^{*} Under normal conditions of use ** Lenticular Envelope *** Standard Envelope

Technical Data

Wind resistance of the balloon	60 mph 100 km/h
Power consumption	700 W
Efficiency	141 lm/W
Voltage	100~240 VAC / 50-60 Hz
Recommended generator	1.5 kVA
Certifications	IEC-60598-1, CE, IP54

Flame-retardant fabric

Airstar Light App

Control your balloons easily and remotely!





Control up to 250 balloons. Max Mesh range between two balloons: up to 109.3 yd - 100 m



4 light animations available









Airstar America Inc. Tel: 1 (800) 217-9001 www.airstar-light.us

