Sirocco 1300



Weight and Dimensions

Net weight of the balloon	20 lbs 9.4 kg
Envelope size	ø 54 in / h 30 in
	ø 138 cm / h 77 cm

Packaging

Included: Lighting balloon with 1x standard envelope (without stand), 1x power cord (30 ft \mid 9.2 m), 1x quick-start guide, 1x envelope repair kit

Transport bag $42 \times 11 \times 11 \text{ in } (L^*w^*h)$ $108 \times 30 \times 30 \text{ cm } (L^*w^*h)$ Transport gross weight $Less \text{ than 36 lbs} \mid 16.5 \text{ kg}$

Recommended Accessories

Stand 15 ft Height from 55 in (140 cm) to 189 in (480 cm)

Weight 30 lbs | 13.5 kg

Sandbag Weight (with sand): 25 lbs (x3 bags recommended)

Main options -----

Envelope options: FLEX (for permanent or long-term use), lenticular, reversed reflector, branded with logo, customized reflector color

132,000





Lighting Data

Light Engine	Airstar LED Matrix: 24 x 5 500 lm
Maximum Lumens	132,000 lm
Average LED Life *	50,000 h
Color Temperature: Daylight	5,000 K
CRI	70
Light under the balloon ** (13 ft high 4 m)	65 fc / 704 lx

Very low risk area

lighting requirement

EN 12464-2 (5 lx)

Technical Data

Standard

Wind resistance of the balloon	60 mph 100 km/h
Power consumption	920 W
Efficiency	143 lm/W
Voltage	100~240 VAC / 50-60 Hz
Recommended generator	2 kVA
Certifications	IEC-60598-1, CE, IP54

Flame-retardant fabric

Airstar Light App

Control your balloons easily and remotely!





Control up to 250 balloons. Max Mesh range between two balloons: up to 109.3 yd - 100 m

Open core area

lighting requirement

EN 1838 (0.5 lx) ***



4 light animations available









Airstar America Inc.
Tel: 1 (800) 217-9001
www.airstar-light.us



^{*} Under normal conditions of use ** Lenticular Envelope *** Standard Envelope