Sirocco 500











Weight and Dimensions

Net weight of the balloon	8.4 lbs 3.8 kg
Envelope size	ø 33 in / h 19 in
	ø 85 cm / h 50 cm

Packaging

Included: Lighting balloon with 1x standard envelope (without stand), 1x power cord (30 ft | 9.2 m), 1x quick-start guide, 1x envelope repair kit

Transport bag	22 x 10 x 10 in (L*w*h)
	$58 \times 25 \times 25 \text{ cm (L*w*h)}$
Transport gross weight	Less than 18.5 lb 8.5 kg

Recommended Accessories

Weight 15 lbs | 6.7 kg

Sandbag Weight (with sand): 25 lbs (x3 bags recommended) Energy Pack 1.7 kWh - 10 hours battery life (PowerSwitch option)

Main options -----



(Battery input 52 V & Backup power)


Provides flexibility in use and installation while ensuring safety (continuity in case of power failure) and bolstering security in work environments to avert accidents

Envelope options: Lenticular, reversed reflector, branded with logo, customized reflector color

Lighting Data

Light Engine	Airstar LED Matrix : 8 x 5 500 lm
Maximum Lumens	44,000 lm
Average LED life *	50,000 h
Color Temperature: Daylight	5,000 K
CRI	70
Light under the balloon **	18 fc / 263 ly





^{*} Under normal conditions of use ** Lenticular Envelope *** Standard Envelope

Technical data

Wind resistance of the balloon	50 mph 80 km/h
Power consumption	294 W
Efficiency	150 lm/W
Voltage	100-240 VAC / 50-60 Hz
Battery voltage (if PowerSwitch option)	52 V
Certifications	IEC-60598-1, CE, IP54

Flame-retardant fabric

Airstar Light App

Control your balloons easily and remotely!





Control up to 250 balloons. Max Mesh range between two balloons: up to 109.3 yd - 100 m



4 light animations available









Airstar America Inc. Tel: 1 (800) 217-9001 www.airstar-light.us

