# Sirocco 700



## Weight and Dimensions

Net weight of the balloon	14 lbs   6.5 kg
Envelope size	ø 39 in / h 19 in
	ø 100 cm / h 50 cm

## **Packaging**

Included: Lighting balloon with 1x standard envelope (without stand), 1x power cord (30 ft | 9.2 m), 1x quick-start guide, 1x envelope repair kit

Transport bag	33 x 11 x 11 in (L*w*h)
	$86 \times 30 \times 30 \text{ cm (L*w*h)}$
Transport gross weight	Less than 29 lbs   13 kg

#### **Recommended Accessories**

Height from 55 in (140 cm) to 189 in (480 cm) Stand 15 ft

Weight 30 lbs | 13.5 kg

Sandbag Weight (with sand): 25 lbs (x3 bags recommended)

#### Main options -----

Envelope options: Lenticular, reversed reflector, branded with logo, customized reflector color






## **Lighting Data**

Light Engine	Airstar LED Matrix: 12 x 5 500 lm
Maximum Lumens	66,000 lm
Average LED Life *	50,000 h
Color Temperature: Daylight	5,000 K
CRI	70
Light under the balloon **	41 fc / 452 lv

(13 ft high | 4 m)



<sup>\*</sup> Under normal conditions of use \*\* Lenticular Envelope \*\*\* Standard Envelope

#### **Technical Data**

Wind resistance of the balloon	60 mph   100 km/h
Power consumption	500 W
Efficiency	132 lm/W
Voltage	100~240 VAC / 50-60 Hz
Recommended generator	1 kVA
Certifications	IEC-60598-1, CE, IP54

Flame-retardant fabric

### Airstar Light App

Control your balloons easily and remotely!





Control up to 250 balloons. Max Mesh range between two balloons: up to 109.3 yd - 100 m



4 light animations available









Airstar America Inc. Tel: 1 (800) 217-9001 www.airstar-light.us

